

DART SERVICE INSTRUCTION

**TO AMEND INSTALLATION INSTRUCTIONS IIN-D119-675 REV. B AND
INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D119-675 REV. 1
REF. FAA STC: SR00948SE**

The removal of OEM crosstube-mounted short steps, described in statement 3.1 of IIN-D119-675 Rev. B and statement 32.2.1 of ICA-D119-675 Rev. 1 should now read:

- a) For **A119 model** aircraft, remove the existing crosstube-mounted short steps (ref. Agusta P/N 109-0570-33-101/-103) by drilling out 4 attachment rivets per step. Plug holes with suitable rivets and touch up paint per the Aircraft Maintenance Manual as required.
- b) For **AW119 MKII model** aircraft, remove the existing crosstube-mounted short steps (ref. Agusta P/N M031-01S002-041) by unfastening the MS21920-20/-22 clamps. Touch up paint per the Aircraft Maintenance Manual as required.

NOTE: It is acceptable to leave the short steps on the landing gear provided they do not interfere with the installation of the Dart step in accordance with the dimensions shown in View A-A of Figure 1 of IIN-D119-675 Rev. B or View A-A of Figure 32-1 of ICA-D119-675 Rev. 1.

A	NEW ISSUE	PH	08.02.28
REV.	DESCRIPTION	BY	DATE
DESIGN	<i>PH</i>	DART AEROSPACE USA, INC. PORT HADLOCK, WA	
DRAWN	<i>PH</i>		
CHECKED	<i>LE</i>	DRAWING NO.	REV. A
MFG. APPR.	<i>N/A</i>	DSI 9407	SHEET 1 OF 1
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	SHORT STEP REMOVAL	NTS
DATE	08.02.28	COPYRIGHT © 2008 BY DART AEROSPACE USA, INC. <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	